

# MultiPrint-M



|                                       |  |
|---------------------------------------|--|
| <b>Cover Type:</b>                    | Rubber   |
| <b>Possible applications:</b>         | Offset printing dampening roll: metering roll, fountain roll etc...<br>Suitable for all dampening systems: with or without alcohol   |
| <b>Hardness Range:</b>                | 25, 30, 35, 40, 45, 50 Shore A   |
| <b>Recommended Cover Thickness:</b>   | min. 10 mm - max. 25 mm  |
| <b>Temperature resistance:</b>        | Dry: continuous 120°C / peak 130°C<br>Wet: continuous 110°C / peak 120°C   |
| <b>Properties and advantages:</b>     | Excellent resistance to oil and grease<br>Very good resistance to abrasion and compression<br>Good heat resistance<br>Good resistance to diluted acids<br>Low resistance to chlorinated solvents and acetates  |
| <b>Chemical resistance:</b>           | Acid solutions: Good<br>Alkaline solutions: Good<br>Hot water and steam: Good<br>Ozone: Very good<br>Oil and grease: Excellent<br>Aromatic solvents (toluene, benzene,...): Moderate<br>Chlorinated solvents: Not suited<br>Polar solvents (MEC, ether, acetate,...): Not suited |
| <b>Recommended cleaning products:</b> | Water and suitable solvents  |