



<b>Cover Type:</b>	Special polyurethane
<b>Possible applications:</b>	Rollers in high temperature environment, combined with high load and/or abrasion - rollers at high temperature and in contact with oily products  Rollers at entry and exit of dryers, ovens and furnaces  Aluminium industry : ironing rollers for cold rolling mills - Steel industry : skin-pass squeegee rollers
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm
<b>Temperature resistance:</b>	Dry: continuous 110°C / peak 130°C Wet: continuous 50°C / peak 60°C
<b>Properties and advantages:</b>	Polyurethane solution with high (dry) temperature resistance  Superior mechanical and dynamical properties, excellent abrasion resistance  Excellent resistance to oil, fuel, kerosene and grease
<b>Chemical resistance:</b>	Acid solutions: Not suited Alkaline solutions: Not suited Hot water and steam: Not suited Ozone: Good Oil and grease: Excellent Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Moderate Polar solvents (MEC, ether, acetate,...): Not suited
<b>Recommended cleaning products:</b>	(Tepid) water, soap, industrial cleaners, cleaning fuel, terpentine, with limited use : alcohol