

# PressoGraf-XP



<b>Cover Type:</b>	Polyurethane	
<b>Possible applications:</b>	Pressure roll for rotogravure printing of flat cardboard, paper, plastic films Packaging, décor	
<b>Hardness Range:</b>	80, 90 Shore A	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 80°C / peak 90°C continuous 50°C / peak 60°C
<b>Properties and advantages:</b>	Excellent abrasion resistance  Very good cut and tear resistance  Excellent resilience.	
<b>Specific characteristics:</b>	Antistatic Surface roughness (Ra):	min. 0.4 µm - max. 6 µm
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...): Ageing resistance:	Moderate Moderate Very good Excellent Good Not suited Moderate Good Excellent Excellent
<b>Recommended cleaning products:</b>	Water, alcohol, IPA, ethyl acetate (no prolonged contact)	