

# NipFoil-S-AS



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Production of plastic films, adhesives and flexible packaging : nip and press rollers, guiding and conveyor rollers, lamination. Contact and lay-on rollers for winding Nip rollers for corona treaters thanks to high antistatic properties.
<b>Hardness Range:</b>	35, 50, 55, 60, 65, 70, 75, 80, 85, 90 Shore A
<b>Recommended Cover Thickness:</b>	min. 6 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 110°C / peak 130°C Wet: continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Bardzo dobre właściwości mechaniczne i dynamiczne.  Neutralne zachowanie w kontakcie z wszelkiego rodzaju foliami z tworzyw sztucznych.  Doskonała odporność na rozpuszczalniki polarne.  Nie zalecany w kontakcie z olejami i smarami
<b>Specific characteristics:</b>	Antistatic
<b>Chemical resistance:</b>	Acid solutions: Excellent Alkaline solutions: Excellent Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent Alcohols (ethanol, IPA,...): Excellent Ageing resistance: Excellent
<b>Recommended cleaning products:</b>	(Hot) water, acid and alkaline cleaners, IPA and alcohol, MEC, ether, ethyl acetate

# NipFoil-S-AS