

# Neostone G



<b>Cover Type:</b>	Special rubber	
<b>Possible applications:</b>	Felt spreading roll (Chevron grooved)	
<b>Hardness Range:</b>	1 PJ	
<b>Recommended Cover Thickness:</b>	Standard 10 mm	min. 5 mm - max. 15 mm
<b>Temperature resistance:</b>	Dry: Wet:	continuous 90°C / peak 100°C continuous 80°C / peak 100°C
<b>Properties and advantages:</b>	Excellent wear resistance Possible to cover roll sides & journals	
<b>Specific characteristics:</b>	Surface roughness (Ra):	min. 1 µm - max. 2.5 µm
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...): Ageing resistance:	Good Good Good Good Good Not suited Moderate Moderate Very good Very good
<b>Recommended cleaning products:</b>	Excellent resistance to chemicals normally involved in forming and press section of paper machines	
<b>Remark:</b>	Do not store below 5°C and avoid thermal shock Reference list available on demand	