



Cover Type:	Rubber	
Possible applications:	<p>All industries : rollers and wheels required in soft rubber, combined with good oil and abrasion resistance</p> <p>Oiling rollers, squeeze rollers, washing and degreasing applications</p>	
Hardness Range:	50, 55, 60, 65, 70 Shore A	
Recommended Cover Thickness:	min. 12 mm - max. 25 mm	
Temperature resistance:	<p>Dry:</p> <p>Wet:</p>	<p>continuous 100°C / peak 110°C</p> <p>continuous 70°C / peak 80°C</p>
Properties and advantages:	<p>Very good resistance to mineral and vegetable oil, grease and animal fat</p> <p>Very good elasticity, resilience and deformability</p> <p>Good mechanical properties and abrasion resistance</p>	
Chemical resistance:	<p>Acid solutions:</p> <p>Alkaline solutions:</p> <p>Hot water and steam:</p> <p>Ozone:</p> <p>Oil and grease:</p> <p>Aromatic solvents (toluene, benzene,...):</p> <p>Chlorinated solvents:</p> <p>Polar solvents (MEC, ether, acetate,...):</p> <p>Alcohols (ethanol, IPA,...):</p>	<p>Moderate</p> <p>Moderate</p> <p>Moderate</p> <p>Very good</p> <p>Excellent</p> <p>Moderate</p> <p>Not suited</p> <p>Not suited</p> <p>Good</p>
Recommended cleaning products:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	