



<b>Cover Type:</b>	Rubber	
<b>Possible applications:</b>	All industries : rollers and wheels required in soft rubber, combined with good oil and abrasion resistance	
	Oiling rollers, squeeze rollers, washing and degreasing applications	
<b>Hardness Range:</b>	50, 55, 60, 65, 70 Shore A	
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 25 mm	
<b>Temperature resistance:</b>	Dry:	continuous 100°C / peak 110°C
	Wet:	continuous 70°C / peak 80°C
<b>Properties and advantages:</b>	Very good resistance to mineral and vegetable oil, grease and animal fat	
	Very good elasticity, resilience and deformability	
	Good mechanical properties and abrasion resistance	
<b>Chemical resistance:</b>	Acid solutions:	Moderate
	Alkaline solutions:	Moderate
	Hot water and steam:	Moderate
	Ozone:	Very good
	Oil and grease:	Excellent
	Aromatic solvents (toluene, benzene,...):	Moderate
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
	Alcohols (ethanol, IPA,...):	Good
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, turpentine, white spirit	