


# Optidraw Plus



<b>Cover Type:</b>	Rubber	
<b>Possible applications:</b>	<p>Production of metal strip : pinch rolls, hold-down rolls, steering, bridle and detour rolls, conveyor rollers, oil distribution and wipe-off rolls, squeegee rolls in different environments</p> <p>Diverse applications in a lot of industrial areas : textile, packaging, (card)board, plastic film, converting, glass, wood etc.</p> <p>Rollers and wheels in contact with oil, fuel or grease, even at higher temperature</p> <p>Finishing of the roller with peach skin</p>	
<b>Hardness Range:</b>	65 Shore A	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm	
<b>Temperature resistance:</b>	Dry:	continuous 90°C / peak 110°C
	Wet:	continuous 60°C / peak 80°C
<b>Properties and advantages:</b>	<p>Excellent resistance to mineral and vegetal oil, fuel, grease and (animal) fat</p> <p>Excellent properties, tear and abrasion resistance, good elasticity and resilience</p> <p>Non-staining in contact with delicate substrates</p> <p>Very good and stable grip in contact with most substrates</p> <p>Very good squeegee and wipe-off behavior</p>	
<b>Chemical resistance:</b>	Acid solutions:	Good
	Alkaline solutions:	Very good
	Hot water and steam:	Good
	Ozone:	Good
	Oil and grease:	Excellent
	Aromatic solvents (toluene, benzene,...):	Good
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	