



<b>Cover Type:</b>	Special rubber	
<b>Possible applications:</b>	<p>Metal strip production and conversion :</p> <ul style="list-style-type: none"><li>- Bridle, steer and deflector rolls, pinch rollers</li><li>- Rollers for metal strip transport where high grip and friction coefficient is needed, transport of humid or oiled strip</li></ul> <p>Textile industry, (Card)board industry, Paper conversion : transport rollers and wheels, tension rollers</p>	
<b>Hardness Range:</b>	75 Shore A	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 90°C / peak 100°C continuous 70°C / peak 80°C
<b>Properties and advantages:</b>	<p>Special rubber with filler increasing the surface roughness after grinding</p> <p>Improved grip and friction coefficient</p> <p>Especially efficient on wet and oil</p>	
<b>Specific characteristics:</b>	Permanent surface roughness	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...):	Moderate Good Not suited Moderate Excellent Moderate Not suited Not suited Very good
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	