

# Reversmaster 3



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Adhesives industry, production of tape and label stock : transfer & applicator rollers & sleeves for silicone coating, applicator and backing rollers for primer coating, cold glue coating  Plastic film & packaging industry : coating rollers for water and solvent based coating
<b>Hardness Range:</b>	70, 80 Shore A
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 100°C / peak 120°C Wet: continuous 70°C / peak 80°C
<b>Properties and advantages:</b>	Low surface energy, low surface roughness  Good abrasion resistance  Dimensional stability throughout the complete lifetime, constant and homogeneous coating quality  Very good chemical compatibility, specifically adapted to polar solvents (MEC, ethyle acetate...)
<b>Chemical resistance:</b>	Acid solutions: Very good Alkaline solutions: Very good Hot water and steam: Very good Ozone: Very good Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent Alcohols (ethanol, IPA,...): Excellent Ageing resistance: Excellent
<b>Recommended cleaning products:</b>	Polar solvents (MEK, ethyl acetate, alcohol...), detergents - avoid hydrocarbons !