



Cover Type:	Special rubber	
Possible applications:	Textile industry : wet finishing processes on fabric : intermediate and final squeegee foulard rollers - specifically suited for dyeing, coating and finishing Suited for Küsters S-Rolls	
Hardness Range:	45, 55, 65, 70, 75, 80, 85, 90 Shore A	
Recommended Cover Thickness:	min. 12 mm - max. 25 mm	
Temperature resistance:	Dry:	continuous 110°C / peak 125°C
	Wet:	continuous 80°C / peak 90°C
Properties and advantages:	Dyeing homogeneity on the entire width of the fabrics Chemical resistance to the main textile auxiliary products Silicate incrustation singularly delayed Easy to clean between 2 treatments Very good abrasion and aging resistance, outstanding lifetime with constant performance Non-staining	
Chemical resistance:	Acid solutions:	Very good
	Alkaline solutions:	Good
	Hot water and steam:	Good
	Ozone:	Excellent
	Oil and grease:	Good
	Aromatic solvents (toluene, benzene,...):	Not suited
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
	Alcohols (ethanol, IPA,...):	Very good
	Ageing resistance:	Excellent
Recommended cleaning products:	(Warm) water, soap, industrial cleaners and detergents, alcohol, acid and alkaline cleaners	
Remark:	Verotex-D : special multilayer solution for demanding applications	