



Cover Type:	Special rubber
Possible applications:	Textile industry : wet finishing processes on fabric : intermediate and final squeegee foulard rollers - specifically suited for dyeing, coating and finishing Suited for Küsters S-Rolls
Hardness Range:	45, 55, 65, 70, 75, 80, 85, 90 Shore A
Recommended Cover Thickness:	min. 12 mm - max. 25 mm
Temperature resistance:	Dry: continuous 110°C / peak 125°C Wet: continuous 80°C / peak 90°C
Properties and advantages:	Dyeing homogeneity on the entire width of the fabrics Chemical resistance to the main textile auxiliary products Silicate incrustation singularly delayed Easy to clean between 2 treatments Very good abrasion and aging resistance, outstanding lifetime with constant performance Non-staining
Chemical resistance:	Acid solutions: Very good Alkaline solutions: Good Hot water and steam: Good Ozone: Excellent Oil and grease: Good Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited Alcohols (ethanol, IPA,...): Very good Ageing resistance: Excellent
Recommended cleaning products:	(Warm) water, soap, industrial cleaners and detergents, alcohol, acid and alkaline cleaners
Remark:	Verotex-D : special multilayer solution for demanding applications